Sales Inquiries: sales@outranger.net
Technical Inquiries: technical@outranger.net

MOTSMANN.COM

2027 Outranger Camper Trailer

SPECIFICATION SHEET

DIMENSIONS

Overall Trailer Dimensions: 162.3 in L × 72.0 in W × 77.8 in maximum H
Maximum height includes the roof rack and factory-installed optional roof equipment

Ground Clearance (under chassis): 19 in
Minimum tongue ground clearance: 15 in

Coupler Height — 19 5/16 in
Ground to bottom of coupler

INTERIOR DIMENSIONS

Floor to ceiling height: 50 in
Standard mattress height 5 in

Mattress dimensions: 82 in L × 57 in W at shoulders / 50 in W lower section
Standard memory foam mattress

Mattress Width: 57 in full length
Mattress height increases by 4 in

WEIGHT AND CAPACITY

Dry Weight: Approximately 1,450 lb in the standard configuration
Dry weight increases as optional equipment is added

Tongue Weight: Approximately 200 lb in the standard configuration
Tongue weight increases as optional equipment is added

Rear Hitch Receiver Capacity: 200 lb maximum accessory load
2" Receiver

Roof Rack Capacity: 150 lb dynamic / 550 lb static
Aluminum roof rack

GVWR: 2,300 lb
Maximum allowable loaded trailer weight, including installed equipment, cargo, water, propane, and provisions

SYSTEMS

Propane Capacity: 10 lb
DOT propane cylinder

Fresh Water Capacity: 14 gal / 30 gal
Electronic level

Holding Tank Capacity: 8 gal
Electronic level

Battery Bank Capacity: 200 Ah / 400 Ah / 600 Ah
Renogy Smart Pro Self-Heating

Solar charging: 200 W solar charging system
Renogy solar panel / Victron MPPT

CHASSIS

Suspension: Timbren 2000HD
Independent trailer suspension

Wheels & Tires: 30 in tires on 15 in wheels
Falken Wildpeak tires

Brakes: 3500 lb electric brakes
Timbren

Coupler: 2 in ball coupler standard / Max Coupler articulating hitch optional
Curt / C U Off Road